



Manual of Standards  
Units of Measurement to be used  
in Air and Ground Operations  
in The Kingdom of Thailand

CAAT-ANS-MOSUM

Issue: 01

Revision: 00

Date: XX Dec 2019

Approved By

---

Chula Sukmanop, PhD

Director General

The Civil Aviation Authority of Thailand

THIS PAGE INTENTIONALLY LEFT BLANK

## Foreword

The General Director of Civil Aviation Authority of Thailand is responsible under Section 16/5 Paragraph 3 of the Air Navigation Act B.E.2497 amended by the Air Navigation Act (No. 14) B.E. 2562 for issuing CAAT regulations on Units of Measurement to be used in Air and Ground Operations in The Kingdom of Thailand to ensure conformity with current and timely International Standards.

The Manual of Standards (hereinafter ‘MOS’) is the means CAAT uses to meet its responsibilities under Section 16/5 Paragraph 3 of the Air Navigation Act B.E.2497 amended by the Air Navigation Act (No. 14) B.E. 2562 and CAAT announcement on Units of Measurement to be used in Air and Ground Operations in The Kingdom of Thailand B.E.2562. The MOS prescribes the detailed of Units of Measurement to be used in Air and Ground Operations.

Readers should forward advice of errors, inconsistencies or suggestions for improvement to this manual to the Manager, Air Navigation Services Standards Department (please see in subsection 1.1.5.3).

The MOS is issued and amended under the authority of the Director General of Civil Aviation Authority of Thailand.

Chula Sukmanop, PhD  
Director General  
The Civil Aviation Authority of Thailand

## Record of Revisions

Issue Number	Revision Number	Effective Date	Revised By	Section Affected
01	00	xx Dec 2019	ANS (IC)	Initial Issue

## List of Effective Pages

page	Revision	date
1-1	00	xx Dec 2019
1-2	00	xx Dec 2019
1-3	00	xx Dec 2019
1-4	00	xx Dec 2019
1-5	00	xx Dec 2019
2-1	00	xx Dec 2019
3-1	00	xx Dec 2019
3-2	00	xx Dec 2019
3-3	00	xx Dec 2019
3-4	00	xx Dec 2019
3-5	00	xx Dec 2019
3-6	00	xx Dec 2019
3-7	00	xx Dec 2019
3-8	00	xx Dec 2019
4-1	00	xx Dec 2019

page	Revision	date

## Table of Contents

Foreword.....	A
Record of Revisions.....	B
List of Effective Pages.....	C
Table of Contents.....	D
Chapter 1 Introduction.....	1-1
1.1 General .....	1-1
1.1.1 Background.....	1-1
1.1.2 Document set.....	1-1
1.1.3 Differences between ICAO Standards and those in MOS.....	1-1
1.1.4 Differences Published in AIP .....	1-1
1.1.5 MOS Documentation Change Management.....	1-1
1.1.6 Related document .....	1-2
1.2 Definitions and Abbreviations.....	1-3
Chapter 2 Applicability.....	2-1
2.1 Applicability .....	2-1
Chapter 3 Standard Application of Units of Measurement .....	3-1
3.1 SI units .....	3-1
3.2 Non-SI Units.....	3-2
3.2.1 Non-SI units for permanent use with the SI .....	3-2
3.2.2 Non-SI alternative units permitted for temporary use with the SI .....	3-2
3.3 Application of specific units.....	3-2
Chapter 4 Termination of use of NON-SI alternative units.....	4-1

## Chapter 1 Introduction

### 1.1 General

#### 1.1.1 Background

1.1.1.1 This MOS is made under the Air Navigation Act B.E.2497 amended by the Air Navigation Act (No. 14) B.E. 2562 refers to the standards of Units of Measurement to be used in Air and Ground Operations.

#### 1.1.2 Document set

1.1.2.1 The document hierarchy consists of:

- a) the Air Navigation Act B.E.2497 amended by the Air Navigation Act (No. 14) B.E. 2562;
- b) The Civil Aviation Authority of Thailand Announcement;
- c) Manual of Standards (MOS).

#### 1.1.3 Differences between ICAO Standards and those in MOS

1.1.3.1 Notwithstanding the above, where there is a difference between a standard prescribed in ICAO documents and the Manual of Standards (MOS), the MOS standard shall prevail.

#### 1.1.4 Differences Published in AIP

1.1.4.1 Differences from ICAO Standards, Recommended Practices and Procedures are published in the AIP Thailand GEN 1.7 Differences from ICAO Standards, Recommended Practices and Procedures.

#### 1.1.5 MOS Documentation Change Management

1.1.5.1 The Air Navigation Services Standards Department (ANS) has responsibility for the technical contents of this MOS.

1.1.5.2 This MOS is issued, and may only be amended, under the authority of the Director General of CAAT.

1.1.5.3 Suggested changes to this MOS may be provided to the Manager of Air Navigation Services Standards Department of CAAT by:

Email: [ans@caat.or.th](mailto:ans@caat.or.th)

1.1.5.4 Requests for any change to the content of this MOS may come from:

- a) technical areas within CAAT; or
- b) aviation industry service providers or operators; or
- c) individuals or authorization holders.

1.1.5.5 The need to change standards in this MOS may arise for any of the following reasons:

- a) to ensure safety;
- b) to ensure standardization;
- c) to respond to changed CAAT standards;
- d) to respond to ICAO prescription;
- e) to accommodate proposed initiatives or new technologies.

#### **1.1.6 Related document**

1.1.6.1 These standards should be read in conjunction with:

- a) The Civil Aviation Authority of Thailand Announcement;
- b) ICAO Annex 5 Units of Measurement to be used in Air and Ground Operations;
- c) AIP Thailand.



## 1.2 Definitions and Abbreviations

1.2.1 For the purpose of this manual of standards, the definition as contained in the ICAO annex and ICAO document, as amended from time to time, shall apply unless as otherwise indicated in AIP or as follow:

Definition	Meaning
<b>Ampere (A).</b>	The ampere is that constant electric current which, if maintained in two straight parallel conductors of infinite length, of negligible circular cross-section, and placed 1 metre apart in a vacuum, would produce between these conductors a force equal to $2 \times 10^{-7}$ newton per metre of length.
<b>Becquerel (Bq).</b>	The activity of a radionuclide having one spontaneous nuclear transition per second.
<b>Candela (cd).</b>	The luminous intensity, in the perpendicular direction, of a surface of 1/600 000 square metre of black body at the temperature of freezing platinum under a pressure of 101 325 newtons per square metre.
<b>Celsius temperature (t°C ).</b>	The Celsius temperature is equal to the difference $t^{\circ}\text{C} = T - T_0$ between two thermodynamic temperatures T and $T_0$ where $T_0$ equals 273.15 kelvin.
<b>Coulomb (C).</b>	The quantity of electricity transported in 1 second by a current of 1 ampere.
<b>Degree Celsius (°C).</b>	The special name for the unit kelvin for use in stating values of Celsius temperature.
<b>Farad (F).</b>	The capacitance of a capacitor between the plates of which there appears a difference of potential of 1 volt when it is charged by a quantity of electricity equal to 1 coulomb.
<b>Foot (ft)..</b>	The length equal to 0.304 8 metre exactly.
<b>Gray (Gy).</b>	The energy imparted by ionizing radiation to a mass of matter corresponding to 1 joule per kilogram.
<b>Henry (H).</b>	The inductance of a closed circuit in which an electromotive force of 1 volt is produced when the electric current in the circuit varies uniformly at a rate of 1 ampere per second.
<b>Hertz (Hz).</b>	The frequency of a periodic phenomenon of which the period is 1 second.
<b>Human performance.</b>	Human capabilities and limitations which have an impact on the safety and efficiency of aeronautical operations.

Definition	Meaning
Joule (J).	The work done when the point of application of a force of 1 newton is displaced a distance of 1 metre in the direction of the force.
Kelvin (K).	A unit of thermodynamic temperature which is the fraction 1/273.16 of the thermodynamic temperature of the triple point of water.
Kilogram (kg).	The unit of mass equal to the mass of the international prototype of the kilogram.
Knot (kt).	The speed equal to 1 nautical mile per hour.
Litre (L).	A unit of volume restricted to the measurement of liquids and gases which is equal to 1 cubic decimetre.
Lumen (lm).	The luminous flux emitted in a solid angle of 1 steradian by a point source having a uniform intensity of 1 candela.
Lux (lx).	The illuminance produced by a luminous flux of 1 lumen uniformly distributed over a surface of 1 square metre.
Metre (m).	The distance travelled by light in a vacuum during 1/299 792 458 of a second.
Mole (mol).	The amount of substance of a system which contains as many elementary entities as there are atoms in 0.012 kilogram of carbon-12. Note.— When the mole is used, the elementary entities must be specified and may be atoms, molecules, ions, electrons, other particles or specified groups of such particles.
Nautical mile (NM).	The length equal to 1 852 metres exactly.
Newton (N).	The force which when applied to a body having a mass of 1 kilogram gives it an acceleration of 1 metre per second squared.
Ohm ( $\Omega$ ).	The electric resistance between two points of a conductor when a constant difference of potential of 1 volt, applied between these two points, produces in this conductor a current of 1 ampere, this conductor not being the source of any electromotive force.
Pascal (Pa).	The pressure or stress of 1 newton per square metre.
Radian (rad).	The plane angle between two radii of a circle which cut off on the circumference an arc equal in length to the radius.
Second (s).	The duration of 9 192 631 770 periods of the radiation corresponding to the transition between the two hyperfine levels of the ground state of the caesium-133 atom.
Siemens (S).	The electric conductance of a conductor in which a current of 1 ampere is produced by an electric potential difference of 1 volt.

Definition	Meaning
<b>Sievert (Sv).</b>	The unit of radiation dose equivalent corresponding to 1 joule per kilogram.
<b>Steradian (sr).</b>	The solid angle which, having its vertex in the centre of a sphere, cuts off an area of the surface of the sphere equal to that of a square with sides of length equal to the radius of the sphere.
<b>Tesla (T).</b>	The magnetic flux density given by a magnetic flux of 1 weber per square metre.
<b>Tonne (t).</b>	The mass equal to 1 000 kilograms.
<b>Volt (V).</b>	The unit of electric potential difference and electromotive force which is the difference of electric potential between two points of a conductor carrying a constant current of 1 ampere, when the power dissipated between these points is equal to 1 watt.
<b>Watt (W).</b>	The power which gives rise to the production of energy at the rate of 1 joule per second.
<b>Weber (Wb).</b>	The magnetic flux which, linking a circuit of one turn, produces in it an electromotive force of 1 volt as it is reduced to zero at a uniform rate in 1 second.

## Chapter 2 Applicability

### 2.1 Applicability

- 2.1.1 This Manual of Standards – Units of Measurement to be used in Air and Ground Operations in The Kingdom of Thailand (hereafter referred to as the “MOS”) shall be applicable to all aspects of international civil aviation air and ground operations in The Kingdom of Thailand.

## Chapter 3 Standard Application of Units of Measurement

### 3.1 SI units

3.1.1 The International System of Units developed and maintained by the General Conference of Weights and Measures (CGPM) shall, subject to the provisions of 3.2 and 3.3, be used as the standard system of units of measurement for all aspects of international civil aviation air and ground operations in The Kingdom of Thailand.

3.1.2 The prefixes and symbols listed in Table 3-1 shall be used to form names and symbols of the decimal multiples and submultiples of SI units.

Note 1.— As used herein the term SI unit is meant to include base units and derived units as well as their multiples and sub-multiples.

Note 2.— See Attachment B of ICAO Annex 5 for guidance on the general application of prefixes.

Table 3-1. SI unit prefixes

<b>Multiplication factor</b>			<b>Prefix</b>	<b>Symbol</b>
1 000 000 000 000 000 000	=	$10^{18}$	exa	E
1 000 000 000 000 000	=	$10^{15}$	peta	P
1 000 000 000 000	=	$10^{12}$	tera	T
1 000 000 000	=	$10^9$	giga	G
1 000 000	=	$10^6$	mega	M
1 000	=	$10^3$	kilo	k
100	=	$10^2$	hecto	h
10	=	$10^1$	deca	da
0.1	=	$10^{-1}$	deci	d
0.01	=	$10^{-2}$	centi	c
0.001	=	$10^{-3}$	milli	m
0.000 001	=	$10^{-6}$	micro	$\mu$
0.000 000 001	=	$10^{-9}$	nano	n
0.000 000 000 001	=	$10^{-12}$	pico	p
0.000 000 000 000 001	=	$10^{-15}$	femto	f
0.000 000 000 000 000 001	=	$10^{-18}$	atto	a

### 3.2 Non-SI Units

#### 3.2.1 Non-SI units for permanent use with the SI

The non-SI units listed in Table 3-2 shall be used either in lieu of, or in addition to, SI units as primary units of measurement but only as specified in Table 3-4.

Table 3-2. Non-SI units for use with the SI

<i>Specific quantities in Table 3-4 related to</i>	<i>Unit</i>	<i>Symbol</i>	<i>Definition (in terms of SI units)</i>
mass	tonne	t	1 t = 10 <sup>3</sup> kg
plane angle	degree	°	1° = (π/180) rad
	minute	'	1' = (1/60)° = (π/10 800) rad
	second	"	1" = (1/60)' = (π/648 000) rad
temperature	degree Celsius	°C	1 unit °C = 1 unit K <sup>a)</sup>
time	minute	min	1 min = 60 s
	hour	h	1 h = 60 min = 3 600 s
	day	d	1 d = 24 h = 86 400 s
	week, month, year	—	
volume	litre	L	1 L = 1 dm <sup>3</sup> = 10 <sup>-3</sup> m <sup>3</sup>

\*a) See table 3-5 for conversion.

#### 3.2.2 Non-SI alternative units permitted for temporary use with the SI

The non-SI units listed in Table 3-3 shall be permitted for temporary use as alternative units of measurement but only for those specific quantities listed in Table 3-4.

Note.— It is intended that the use of the non-SI alternative units listed in Table 3-3 and applied as indicated in Table 3-4 will eventually be discontinued in accordance with individual unit termination dates established by the Council. Termination dates, when established, will be given in Chapter 4.

### 3.3 Application of specific units

3.3.1 The application of units of measurements for certain quantities used in international civil aviation air and ground operations in The Kingdom of Thailand shall be in accordance with Table 3-4.

3.3.2 Means and provisions for design, procedures and training should be established for operations in environments involving the use of standard and non-SI units of measurement, or the transition between environments using different units, with due consideration to human performance.

Note.— Guidance material on human performance can be found in the Human Factors Training Manual (Doc 9683).

Table 3-3. Non-SI alternative units permitted for temporary use with the SI

<i>Specific quantities in Table 3-4 related to</i>	<i>Unit</i>	<i>Symbol</i>	<i>Definition (in terms of SI units)</i>
distance (long)	nautical mile	NM	1 NM = 1 852 m
distance (vertical) <sup>a)</sup>	foot	ft	1 ft = 0.304 8 m
speed	knot	kt	1 kt = 0.514 444 m/s

a) altitude, elevation, height, vertical speed.

Table 3-4. Standard application of specific units of measurement

Ref. No.	Quantity	Primary Unit (Symbol)	Non-SI Alternative Unit (Symbol)
1.Direction/Space/Time			
1.1	altitude	m	ft
1.2	area	m <sup>2</sup>	
1.3	distance (long) <sup>a)</sup>	km	NM
1.4	distance (short)	m	
1.5	elevation	m	ft
1.6	endurance	h and min	
1.7	height	m	ft
1.8	latitude	° ‘ “	
1.9	length	m	
1.10	longitude	° ‘ “	
1.11	plane angle (when required, decimal subdivisions of the degree shall be used)	°	

Ref. No.	Quantity	Primary Unit (Symbol)	Non-SI Alternative Unit (Symbol)
1.12	runway length	m	
1.13	runway visual range	m	
1.14	tank capacities (aircraft) <sup>b)</sup>	L	
1.15	time	s min h d week month year	
1.16	visibility <sup>c)</sup>	km	
1.17	volume	m <sup>3</sup>	
1.18	wind direction (wind directions other than for a landing and take-off shall be expressed in degrees true; for landing and take-off wind directions shall be expressed in degrees magnetic)	°	
<b>2. Mass-related</b>			
2.1	air density	kg/m <sup>3</sup>	
2.2	area density	kg/m <sup>2</sup>	
2.3	cargo capacity	kg	
2.4	cargo density	kg/m <sup>3</sup>	
2.5	density (mass density)	kg/m <sup>2</sup>	
2.6	fuel capacity (gravimetric)	kg	
2.7	gas density	kg/m <sup>3</sup>	
2.8	gross mass or payload	kg t	
2.9	hoisting provisions	kg	
2.10	linear density	kg/m	
2.11	liquid density	kg/m <sup>3</sup>	
2.12	mass	kg	
2.13	moment of inertia	kg.m <sup>2</sup>	



Ref. No.	Quantity	Primary Unit (Symbol)	Non-SI Alternative Unit (Symbol)
2.14	moment of momentum	kg.m <sup>2</sup> /s	
2.15	momentum	kg.m/s	
<b>3. Force-related</b>			
3.1	air pressure (general)	kPa	
3.2	altimeter setting	hPa	
3.3	atmospheric pressure	hPa	
3.4	bending moment	kN.m	
3.5	force	N	
3.6	fuel supply pressure	kPa	
3.7	hydraulic pressure	kPa	
3.8	modulus of elasticity	MPa	
3.9	pressure	kPa	
3.10	stress	MPa	
3.11	surface tension	mN/m	
3.12	thrust	kN	
3.13	torque	N.m	
3.14	vacuum	Pa	
<b>4. Mechanics</b>			
4.1	airspeed <sup>d)</sup>	km/h	kt
4.2	angular acceleration	rad/s <sup>2</sup>	
4.3	angular velocity	rad/s	
4.4	energy or work	J	
4.5	equivalent shaft power	kW	
4.6	frequency	Hz	
4.7	ground speed	km/h	kt
4.8	impact	J/m <sup>2</sup>	
4.9	kinetic energy absorbed by brakes	MJ	
4.10	linear acceleration	m/s <sup>2</sup>	
4.11	power	kW	
4.12	rate of trim	°/s	
4.13	shaft power	kW	
4.14	velocity	m/s	
4.15	vertical speed	m/s	ft/min

Ref. No.	Quantity	Primary Unit (Symbol)	Non-SI Alternative Unit (Symbol)
4.16	wind speed <sup>e)</sup>	m/s	kt
<b>5. Flow</b>			
5.1	engine airflow	kg/s	
5.2	engine waterflow	kg/h	
5.3	fuel consumption (specific)		
	piston engines	kg/(kW.h)	
	turbo-shaft engines	kg/(kW.h)	
	jet engines	kg/(kN.h)	
5.4	fuel flow	kg/h	
5.5	fuel tank filling rate (gravimetric)	kg/min	
5.6	gas flow	kg/s	
5.7	liquid flow (gravimetric)	g/s	
5.8	liquid flow (volumetric)	L/s	
5.9	mass flow	kg/s	
5.10	oil consumption		
	gas turbine	kg/h	
	piston engines (specific)	g/(kW.h)	
5.11	oil flow	g/s	
5.12	pump capacity	L/min	
5.13	ventilation airflow	m <sup>3</sup> /min	
5.14	viscosity (dynamic)	Pa.s	
5.15	viscosity (kinematic)	m <sup>2</sup> /s	
<b>6. Thermodynamics</b>			
6.1	coefficient of heat transfer	W/(m <sup>2</sup> .K)	
6.2	heat flow per unit area	J/m <sup>2</sup>	
6.3	heat flow rate	W	
6.4	humidity (absolute)	g/Kg	
6.5	coefficient of linear expansion	°C <sup>-1</sup>	
6.6	quantity of heat	J	
6.7	temperature	°C	
<b>7. Electricity and magnetism</b>			
7.1	capacitance	F	

Ref. No.	Quantity	Primary Unit (Symbol)	Non-SI Alternative Unit (Symbol)
7.2	conductance	S	
7.3	conductivity	S/m	
7.4	current density	A/m <sup>2</sup>	
7.5	electric current	A	
7.6	electric field strength	C/m <sup>2</sup>	
7.7	electric potential	V	
7.8	electromotive force	V	
7.9	magnetic field strength	A/m	
7.10	magnetic flux	Wb	
7.11	magnetic flux density	T	
7.12	power	W	
7.13	quantity of electricity	C	
7.14	resistance	Ω	
<b>8. Light and related electromagnetic radiations</b>			
8.1	illuminance	lx	
8.2	luminance	cd/m <sup>2</sup>	
8.3	luminous exitance	lm/m <sup>2</sup>	
8.4	luminous flux	lm	
8.5	luminous intensity	cd	
8.6	quantity of light	lm.s	
8.7	radiant energy	J	
8.8	wavelength	m	
<b>9. Acoustics</b>			
9.1	frequency	Hz	
9.2	mass density	kg/m <sup>3</sup>	
9.3	noise level	dB <sup>e)</sup>	
9.4	period, periodic time	s	
9.5	sound intensity	W/m <sup>2</sup>	
9.6	sound power	W	
9.7	sound pressure	Pa	
9.8	sound level	dB <sup>f)</sup>	

Ref. No.	Quantity	Primary Unit (Symbol)	Non-SI Alternative Unit (Symbol)
9.9	static pressure (instantaneous)	Pa	
9.10	velocity of sound	m/s	
9.11	volume velocity (instantaneous)	m <sup>3</sup> /s	
9.12	wavelength	m	
<b>10. Nuclear physics and ionizing radiation</b>			
10.1	absorbed dose	Gy	
10.2	absorbed dose rate	Gy/s	
10.3	activity of radionuclides	Bq	
10.4	dose equivalent	Sv	
10.5	radiation exposure	C/kg	
10.6	exposure rate	C/kg.s	

- a) As used in navigation, generally in excess of 4 000 m.
- b) Such as aircraft fuel, hydraulic fluids, water, oil and high pressure oxygen vessels.
- c) Visibility of less than 5 km may be given in m.
- d) Airspeed is sometimes reported in flight operations in terms of the ratio MACH number.
- e) A conversion of 1 kt = 0.5 m/s is used in ICAO Annexes for the representation of wind speed.
- f) The decibel (dB) is a ratio which may be used as a unit for expressing sound pressure level and sound power level. When used, the reference level must be specified.

Table 3-5 Temperature conversion formulae

<i>To convert from</i>	<i>to</i>	<i>Use formula</i>
Celsius temperature (t <sup>°C</sup> )	Kelvin temperature (t <sub>K</sub> )	t <sub>K</sub> = t <sup>°C</sup> + 273.15
Fahrenheit temperature (t <sup>°F</sup> )	Celsius temperature (t <sup>°C</sup> )	t <sup>°C</sup> = (t <sup>°F</sup> - 32)/1.8
Fahrenheit temperature (t <sup>°F</sup> )	Kelvin temperature (t <sub>K</sub> )	t <sub>K</sub> = (t <sup>°F</sup> + 459.67)/1.8
Kelvin temperature (t <sub>K</sub> )	Celsius temperature (t <sup>°C</sup> )	t <sup>°C</sup> = t <sub>K</sub> - 273.15
Rankine temperature (t <sup>°R</sup> )	Kelvin temperature (t <sub>K</sub> )	t <sub>K</sub> = t <sup>°R</sup> /1.8

## Chapter 4 Termination of use of NON-SI alternative units

4.1 The use in international civil aviation operations of the alternative non-SI units listed in Table 3-3 shall be terminated on the dates listed in Table 4-1.

Note.- The non-SI units listed in Table 3-3 have been retained temporarily for use as the units because of their widespread use and to avoid potential safety problems which could result from the lack of international coordination concerning the termination of their use. As termination dates are established by the ICAO Council, they will be reflected as Standards contained in this Chapter: It is expected that the establishment of such dates will be well in advance of actual termination. Any special procedures associated with specific unit termination will be circulated separately from this Manual of Standards.

Table 4-1. Termination dates for non-SI alternative units

<i>Non-SI alternative unit</i>	<i>Termination date</i>
Knot Nautical mile	not established <sup>a)</sup>
Foot	not established <sup>b)</sup>

a) No termination date has yet been established for use of nautical mile and knot.  
 b) No termination date has yet been established for use of the foot.